



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

* 1 Identification

: Product identifier

: Trade name: **Unisol® Liquid Red BK-50**

: Application of the substance / the mixture Dyestuff/Coloring agent

: Details of the supplier of the safety data sheet

: Manufacturer/Supplier:

United Color Manufacturing, Inc.
660 Newtown-Yardley Road
Newtown, PA 18940 USA

: For more information Website: www.unitedcolor.com

: Telephone: U.S. (215) 860-2165 / 800-852-5942

: Emergency telephone number:

Within Continental U.S., CHEMTREC 1-800-424-9300
Outside U.S., CHEMTREC +1-703-527-3887

2 Hazard(s) identification

: Classification of the substance or mixture



Flame

Flammable liquid and vapor.



Health hazard

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.



Environment

Toxic to aquatic life with long lasting effects.



Causes skin irritation.

May cause respiratory irritation. May cause drowsiness or dizziness.

: Label elements

: GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

: Hazard pictograms



GHS02



GHS07



GHS08



GHS09

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 1)

: **Signal word** Danger

: **Hazard-determining components of labeling:**

xylene

2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar"-Me derivs.

ethylbenzene

Kerosene (petroleum)

: **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

: **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

: **Classification system:**

: **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 2)

: **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

: **Other hazards**: **Results of PBT and vPvB assessment**: **PBT:** Not applicable.: **vPvB:** Not applicable.

3 Composition/information on ingredients

: **Chemical characterization: Mixtures**: **Description:** Mixture of the substances listed below with nonhazardous additions.: **Dangerous components:**

92257-31-3	2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazanyl]-, ar-heptyl ar',ar''-Me derivs.	30-40%
1330-20-7	xylene	25-35%
8008-20-6	Kerosene (petroleum)	20-30%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	10-20%
100-41-4	ethylbenzene	5-20%

: **Additional information:** EPA Accession number 35371

4 First-aid measures

: **Description of first aid measures**: **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

: **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.: **After skin contact:** Immediately wash with water and soap and rinse thoroughly.: **After eye contact:** Rinse opened eye for several minutes under running water.: **After swallowing:** Immediately call a doctor.: **Information for doctor:**: **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

: **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

: **Extinguishing media**: **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.: **For safety reasons unsuitable extinguishing agents:** Water with full jet: **Special hazards arising from the substance or mixture** No further relevant information available.: **Advice for firefighters**: **Protective equipment:** No special measures required.

6 Accidental release measures

: **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

: **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 3)

: **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

: **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

: **Handling:**

: **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

: **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Keep respiratory protective device available.

: **Conditions for safe storage, including any incompatibilities**

: **Storage:**

: **Requirements to be met by storerooms and receptacles:** No special requirements.
: **Information about storage in one common storage facility:** Not required.
: **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.

: **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

: **Additional information about design of technical systems:** No further data; see item 7.

: **Control parameters**

: **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

8008-20-6 Kerosene (petroleum)

REL	Long-term value: 100 mg/m ³ Kerosine only
TLV	Long-term value: 200 mg/m ³ as total hydrocarbon vapor; Skin; P

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm

(Contd. on page 5)

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 4)

TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI
: Ingredients with biological limit values:	
1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-41-4 ethylbenzene	
BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

: Additional information: The lists that were valid during the creation were used as basis.

: Exposure controls

: Personal protective equipment:

: General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

: Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

: Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

: Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

: Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 5)

: Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

: Information on basic physical and chemical properties	
: General Information	
: Appearance:	
: Form:	Fluid
: Color:	Red
: Odor:	Aromatic
: Odour threshold:	Not determined.
: pH-value:	Not determined.
: Change in condition	
: Melting point/Melting range:	Undetermined.
: Boiling point/Boiling range:	137 °C (279 °F)
: Flash point:	> 35 °C (> 95 °F)
: Flammability (solid, gaseous):	Not applicable.
: Ignition temperature:	254 °C (489 °F)
: Decomposition temperature:	Not determined.
: Auto igniting:	Product is not selfigniting.
: Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
: Explosion limits:	
: Lower:	0.7 Vol %
: Upper:	7.0 Vol %
: Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
: Density:	Not determined.
: Relative density	Not determined.
: Vapour density	Not determined.
: Evaporation rate	Not determined.
: Solubility in / Miscibility with	
: Water:	Not miscible or difficult to mix.
: Partition coefficient (n-octanol/water): Not determined.	
: Viscosity:	
: Dynamic:	Not determined.
: Kinematic:	Not determined.
: Solvent content:	
: Organic solvents:	32.6 %
: VOC content:	32.6 %
: Solids content:	30.9 %
: Other information	No further relevant information available.

(Contd. on page 7)



Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 6)

10 Stability and reactivity

- : **Reactivity**
- : **Chemical stability**
 - : **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- : **Possibility of hazardous reactions** No dangerous reactions known.
- : **Conditions to avoid** No further relevant information available.
- : **Incompatible materials:** No further relevant information available.
- : **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- : **Information on toxicological effects**
- : **Acute toxicity:**

: **LD/LC50 values that are relevant for classification:**

92257-31-3 2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
------	------	------------------

Dermal	LD50	2000 mg/kg (rabbit)
--------	------	---------------------

8008-20-6 Kerosene (petroleum)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

Inhalative	LC50/4 h	>5000 mg/l (rat)
------------	----------	------------------

64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral	LD50	>5000 mg/kg (rat) (OECD Guideline 401)
------	------	--

Dermal	LD50	>2000 mg/kg (rabbit) (OECD Guideline 402)
--------	------	---

Inhalative	LC50/4 h	4778 mg/l (rat) (OECD Guideline 403)
------------	----------	--------------------------------------

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
------	------	------------------

Dermal	LD50	17800 mg/kg (rabbit)
--------	------	----------------------

- : **Primary irritant effect:**
 - : **on the skin:** Irritant to skin and mucous membranes.
 - : **on the eye:** No irritating effect.
- : **Sensitization:** No sensitizing effects known.

: **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

: **Carcinogenic Status:**

Contains an o-Toluidine-based azo dye. Metabolic studies on some Azo-dyes, following prolonged skin or oral cavity contact, have detected reduction of azo bonds to aromatic amines. This product, therefore, could potentially metabolize to o-toluidine and o-aminoazotoluene upon prolonged skin or oral cavity contact. o-Toluidine and o-aminoazotoluene have been identified as animal carcinogens.

: **Reproductive effects:**

(Contd. on page 8)



Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 7)

May affect reproductive system. Contains: a version of 2-Naphthalenol,1-[[4-(phenylazo)phenyl]azo]-,ar-heptyl ar',ar''-me derivatives. A reproductive screening study in rats with some versions of 2-Naphthalenol,1-[[4-(phenylazo)phenyl]azo]-,ar-heptyl ar',ar''-me derivatives produced adverse effects on reproduction [ovarian atrophy; reduced litter size; reduced pup weight with no apparent abnormal morphology of the surviving pups] at 20 and 80 mg/kg/day. The relevance of these findings for humans is uncertain, but may be predictive of the potential to cause harm.

: Carcinogenic categories

: IARC (International Agency for Research on Cancer)		
1330-20-7	xylene	3
8008-20-6	Kerosene (petroleum)	2B
100-41-4	ethylbenzene	2B
: NTP (National Toxicology Program)		
None of the ingredients is listed.		
: OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

: Toxicity

: Aquatic toxicity:		
8008-20-6 Kerosene (petroleum)		
	EC50	10-100 mg/kg (Algae) 10-100 mg/kg (daphnia) 10-100 mg/kg (fish)
64742-94-5 Solvent naphtha (petroleum), heavy arom.		
Oral	LC50 aquatic	3.6 mg/l (Oncorhynchus mykiss)
	EC50	3.6 mg/kg (Oncorhynchus mykiss) (96 hr)
100-41-4 ethylbenzene		
	EC50	3.6 mg/kg (Algae) 1.81 mg/kg (daphnia) 4.2 mg/kg (fish)

: Persistence and degradability No further relevant information available.

: Behavior in environmental systems:

: Bioaccumulative potential No further relevant information available.

: Mobility in soil No further relevant information available.

: Ecotoxicological effects:

: Remark: Toxic for fish

: Additional ecological information:

: General notes:

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

: Results of PBT and vPvB assessment

: PBT: Not applicable.

: vPvB: Not applicable.

: Other adverse effects No further relevant information available.

(Contd. on page 9)

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 8)

13 Disposal considerations

- : Waste treatment methods**
- : Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- : Uncleaned packagings:**
- : Recommendation:** Disposal must be made according to official regulations.

14 Transport information

: UN-Number	
: DOT, IMDG, IATA	UN1993
: UN proper shipping name	
: DOT	Flammable liquids, n.o.s. (Kerosene (petroleum), Xylenes)
: IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Kerosene (petroleum), XYLENES)
: Transport hazard class(es)	
: DOT	
	
: Class	3 Flammable liquids
: Label	3
: IMDG, IATA	
	
: Class	3 Flammable liquids
: Label	3
: Packing group	
: DOT, IMDG, IATA	III
: Environmental hazards:	Product contains environmentally hazardous substances: Naphthalene
: Marine pollutant:	No
: Special precautions for user	Warning: Flammable liquids
: Danger code (Kemler):	30
: EMS Number:	F-E,S-E
: Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
: Transport/Additional information:	
: DOT	
: Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: **Unisol® Liquid Red BK-50**

(Contd. of page 9)

: IMDG	
: Limited quantities (LQ)	5L
: Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
: UN "Model Regulation":	UN1993, Flammable liquids, n.o.s. (Kerosene (petroleum), Xylenes), ENVIRONMENTALLY HAZARDOUS, 3, III

15 Regulatory information

: Safety, health and environmental regulations/legislation specific for the substance or mixture
: Sara

: Section 355 (extremely hazardous substances):

None of the ingredients is listed.

: Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

: Sara 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

None of the ingredients is listed.

: CERCLA Hazardous Substances and Corresponding RQ's

1330-20-7 xylene

100 lbs or 45.4 kgs

100-41-4 ethylbenzene

1000 lbs or 454 kgs

91-20-3 Naphthalene

100 lbs or 45.4 kgs

: Clean Water Act

None of the ingredients is listed.

: Massachusetts Extraordinary Harardous Substances

None of the ingredients is listed.

: Sara Section 302 (Reportable Ingredients)

None of the ingredients is listed.

: SARA Section 304 (Reportable Ingredients)

None of the ingredients is listed.

: TSCA (Toxic Substances Control Act):

All ingredients are listed.

: California Right to Know Law

1330-20-7 xylene

Yes

100-41-4 ethylbenzene

Yes

91-20-3 Naphthalene

Yes

: Massachusetts Right to Know Law

1330-20-7 xylene

Yes

100-41-4 ethylbenzene

Yes

: Minnesota Right to Know Law

1330-20-7 xylene

Yes

100-41-4 ethylbenzene

Yes

(Contd. on page 11)

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 10)

: New Jersey Right to Know Law		
1330-20-7	xylene	
100-41-4	ethylbenzene	
: Pennsylvania Right to Know Law		
1330-20-7	xylene	Yes
64742-94-5	Solvent naphtha (petroleum), heavy arom.	Yes
100-41-4	ethylbenzene	Yes
: Rhode Island Right to Know Law		
1330-20-7	xylene	Yes
100-41-4	ethylbenzene	Yes
: New Jersey Special Hazardous Substances		
91-20-3	Naphthalene	
: Illinois Toxic Air Contaminants		
91-20-3	Naphthalene	
: Pennsylvania Special Hazardous Substances		
91-20-3	Naphthalene	
: Proposition 65		
: Chemicals known to cause cancer:		
100-41-4	ethylbenzene	
91-20-3	Naphthalene	
: Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
: Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
: Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
: Carcinogenic categories		
: EPA (Environmental Protection Agency)		
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
: TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene	A4
8008-20-6	Kerosene (petroleum)	A3
100-41-4	ethylbenzene	A3
: NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

: GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

: Hazard pictograms



(Contd. on page 12)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 11)

: **Signal word** Danger

: **Hazard-determining components of labeling:**

xylene

2-Naphthalenol, 1-[2-[4-(2-phenyldiazenyl)phenyl]diazenyl]-, ar-heptyl ar',ar''-Me derivs.

ethylbenzene

Kerosene (petroleum)

: **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

: **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear protective gloves / protective clothing.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

: **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

: **Department issuing SDS:** Regulatory Affairs department.

: **Contact:** J. Frederico, Ph.D

: **Date of preparation / last revision** 06/10/2015 / -

(Contd. on page 13)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/10/2015

Reviewed on 06/10/2015

Trade name: Unisol® Liquid Red BK-50

(Contd. of page 12)

: Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

: * Data compared to the previous version altered.